

# Rechargeable NiMH Button Cells



**VARTA Microbattery** combines entrepreneurial substance, strategic visions and technological competency for constantly improved products, application oriented designs and innovative product development. For more information please visit our internet page [www.varta-microbattery.com](http://www.varta-microbattery.com).

## Capacity Range

From V 6 HR to V 600 HRT, from 6 mAh up to 600 mAh – **VARTA** provides a full programme of rechargeable button cells for all performance requirements.

## Key Features – Benefits

- Safety: built-in pressure vent guarantees safety in case of mistreatment
- Low self discharge: no handling, no charging – ready to use after storage due to superior self discharge performance
- Cycle Life: extended product life time of more than 1000 cycles (IEC)
- Overcharge capability: cost effective charging system with no need for special components due to patented GCE electrode
- Deep discharge capability: longer lasting shelf-life with high capacity retention after deep discharge
- No leakage: direct mounting on PCB possible due to patented crimp sealing system

### V...H robust

High performance button cell with superior overcharge stability and discharge currents  $\leq 2$  CA. Based on mass electrode technology, temperature range  $-20^{\circ}\text{C}$  to  $+65^{\circ}\text{C}$ .

Typical Applications:

- Memory Backup
- Real Time Clock
- Mobile Light

Type Designation	Type No.	Voltage (V)	Capacity (mAh)
V 15 H	55602	1.2	16
V 40 H	55604	1.2	43
V 80 H	55608	1.2	80
V 150 H	55615	1.2	150
V 200 H	55620	1.2	210
V 250 H	55625	1.2	250
CP 300 H	55630	1.2	300

### V...HT robust85C

High performance button cell with superior overcharge stability and discharge currents  $\leq 2$  CA at high temperature. Based on mass electrode technology, temperature range  $-20^{\circ}\text{C}$  to  $+85^{\circ}\text{C}$ .

Typical Applications:

- Industrial Electronics
- Automotive Applications

Type Designation	Type No.	Voltage (V)	Capacity (mAh)
V 65 HT	55707	1.2	70
V 150 HT	55716	1.2	150

Application V...H

Application V...HT



## Quality – Made in Germany

- Manufactured on highly automated lines
- Direct replacement for Ni-Cd
- No memory effect
- 0% lead, 0% mercury and 0% cadmium
- UL recognition under file BBET2.MH13654

## Battery Guide

Four button cell families with specific strengths and features provide the ideal battery solution for any application.

	self discharge	overcharge	deep discharge	cycle life	storage behaviour	high rate capacity	charge efficiency at high temp.	temperature range
V...H robust	++	++	++	+++	++	+	+	+
V...HT robust85C	++	+++	++	+++	++	+	++	++
V...HR powerful	+	+	+	+++	+	+++	+	+
V...HRT powerful85C	+	+	+	+++	+	++	++	++

### V..HR powerful

High rate button cell with superior load capability for discharge currents up to 5 CA. Based on foam electrode technology, temperature range -20°C to +65°C.

Typical Applications:

- Consumer Electronics
- Health Care Devices
- Wireless Headsets, Headphones

Type Designation	Type No.	Voltage (V)	Capacity (mAh)
V 6 HR	55996	1.2	6.2
V 450 HR	55945	1.2	450.0
V 600 HR	55960	1.2	600.0

### V...HRT powerful85C

High rate and high temperature button cell with superior load capability for discharge currents up to 5 CA at high temperature. Based on foam electrode technology, temperature range -20°C to +85°C.

Typical Applications:

- Automotive Electronics
- Server, Computer
- Emergency Light, Solar Light

Type Designation	Type No.	Voltage (V)	Capacity (mAh)
V 18 HRT	55802	1.2	19
V 150 PT	55815	1.2	150
V 500 HT	55750	1.2	510
V 550 HRA	55855	1.2	550
V 600 HRT	55860	1.2	600

Application V...HR



Application V...HRT



Single cell or assembled power pack –  
**VARTA** Button Cells for every application!

## Product Overview

Type Designation	Type No.	Voltage (V)	Capacity (mAh)	Diameter (mm)	Height (mm)	Length (mm)	Width (mm)	Weight (g)
<b>V...H robust</b>								
V 15 H	55602	1.2	16.0	11.5	3.10			1.30
V 40 H	55604	1.2	43.0	11.5	5.35			1.70
V 80 H	55608	1.2	80.0	15.5	6.00			4.00
V 150 H	55615	1.2	150.0		5.85	14.1	25.6	6.00
V 200 H	55620	1.2	210.0		7.40	14.1	25.6	7.00
V 250 H	55625	1.2	250.0	25.1	6.70			10.00
CP 300 H	55630	1.2	300.0	25.1	7.55			11.00
<b>V...HT robust85C</b>								
V 65 HT	55707	1.2	70.0	15.5	6.00			4.00
V 150 HT	55716	1.2	150.0		5.85	14.1	25.6	6.00
<b>V...HR powerful</b>								
V 6 HR	55996	1.2	6.2	6.8	2.15			0.28
V 450 HR	55945	1.2	450.0		5.60	24.1	34.1	12.50
V 600 HR	55960	1.2	600.0		6.80	24.1	34.1	14.50
<b>V...HRT powerful85C</b>								
V 18 HRT	55802	1.2	19.0	11.5	2.30			0.90
V 150 PT	55815	1.2	150.0		3.60	24.1	34.1	7.50
V 500 HT	55750	1.2	510.0		6.60	24.2	34.1	14.00
V 550 HRA	55855	1.2	550.0		6.80	24.1	34.1	14.50
V 600 HRT	55860	1.2	600.0		6.80	24.1	34.1	14.50

Voltage and Capacity indicated refer to nominal and typical values respectively.

## Contact

### Headquarters

VARTA Microbattery GmbH, Daimlerstr. 1, 73479 Ellwangen, Germany

### Germany

VARTA Microbattery GmbH  
Daimlerstr. 1, 73479 Ellwangen, Germany  
Tel +49 7961 921-0  
Fax +49 7961 921-553

### Americas

VARTA Microbattery Inc.  
555 Theodore Fremd Avenue  
Suite C 304 Rye, NY 10580, USA  
Tel +1 914 592 25 00  
Fax +1 914 345 04 88

### Asia Pacific

VARTA Microbattery Pte. Ltd.  
300 Tampines Avenue 5, #05-01 Income  
@ Tampines Junction, 529653 Singapore  
529653 Singapore  
Tel +65 6 260 58 01  
Fax +65 6 260 58 12

VARTA Microbattery GmbH is a company of VARTA AG.



[www.varta-microbattery.com](http://www.varta-microbattery.com)